

## Parallelverbinder, KS-Verbinder

parallel connectors for two rods with one or two screws; KS connector clamping screw for lightning current carrying capable connection of round conductors to flat profiles, made from hot-dip galvanized steel, inox or copper

### Parallelverbinder (PV) für Runddrähte



- 140048 **PV 10/TG fz Temperguss feuerverzinkt** (TG fz),  
2xSK-/Schlitz-Schr.M8x25, 2xRD5-10 bzw. STS95<sup>2</sup>, 48x38mm, VE 50, 0,125kg
- 140381 **PV 4-10/Cu** Kupfer, 2x NIRO-SK-Schraube M8x30,  
2x RD4-10mm (ca.50-78mm<sup>2</sup>), 50x49mm, 13,6kA, VE 50, 0,151kg
- 140011 **PV 10/fz** Stahl fz, 2x SK-Schraube M8,  
2xRD7-10 bzw.STS95<sup>2</sup>, H, VE 50, 0,12kg
- 140410 **PV 6-22/St-bl** Stahl blank, 1x Schraube M10x40,  
2xRD 8-22, VE 50, 0,16kg

### KS-Verbinder (Klemmschrauben-Verbinder) 1-fach und 2-fach

- 140071 KS-Verbinder St fz/ZG, 1xRD7-10, für oberirdische Verwendung, (H), VE 100, 0,07kg
- 140157 KS-Verbinder St fz/ZG, 2xRD7-10, für oberirdische Verwendung, n.EN50164-1, VE 25, 0,13kg
- 140377 KS-Verbinder NIRO V4A, 1x RD8-10, VE 100, 0,07kg
- 140420 KS-Verbinder Cu/RG, 1x RD6-10, 25-70mm<sup>2</sup>, M10, Schraube, Mutter u. Federring, EN62561-1

